


# SPG07

## Planetary gearhead



Dimension in mm

Note) Dimension marked ※ is measured with shaft pushed against gearhead.

**For combination with motors: SCL07-17, SBL07-12**

### General specifications

	SPG07	
Housing material	Metal	
Geartrain material	Steel	
Recommended max. input speed	12000	rpm
Operating temperature range	-10...+60	°C
Backlash at no-load per stage	≤ 1	°
Bearings on output shaft	Sintered sleeve bearings	
Max. shaft radial load (4.5 mm from flange)	1	N
Max. shaft axial load	0.5	N
Max. shaft press fit force	10	N
Shaft radial play	≤ 0.03	mm
Shaft axial play	≤ 0.3	mm

Ratio (nominal)	Stage	Gearhead length, L1 [mm]	Gearhead weight [g]	Max. allowable torque [mNm]		Length with motor [mm]				Efficiency [%]	Direction of rotation		
				Continuous	Intermittent	SCL07-17	SBL07-12						
4.7 : 1	1	7.4	2	10	20	24.9	19.4					85	=
22 : 1	2	9.6	2.5	10	20	27.1	21.6					72	=
105 : 1	3	11.8	3	10	20	29.3	23.8					61	=
494 : 1	4	14.1	3.5	10	20	31.6	26.1					52	=

### V01

Namiki Precision Jewel Co.,Ltd

TEL: +81-3-5390-7619 FAX: +81-3-5390-8082


URL: www.namiki.net/

E-mail: kboinfo@namiki.net

Specifications subject to change without notice

# SSD07

## Sensorless brushless motor drive circuit



For DC brushless motor serie SBL07-12

### Description

SSD07 is a 3-phase sensorless drive circuit designed to operate brushless motor SBL07-12 exclusively. The operating voltage can be adjusted by VR trimmer and motor shaft direction can be reversed by connecting CW/CCW input to Vcc, if not connected the motor runs CW. FG (Frequency Generator) output provides a pulse per motor revolution. Internal thermal protection circuit included.

### Specifications

	SSD07			
	Min.	Typ.	Max.	
Voltage supply	2.7		6.0	V
Output voltage			4.9	V
Output current			0.8	A
Operating temperature range	-20...+75			°C
Weight	1.9			g

V01

Namiki Precision Jewel Co.,Ltd

TEL: +81-3-5390-7619 FAX: +81-3-5390-8082

URL: [www.namiki.net/](http://www.namiki.net/)

E-mail: [kboinfo@namiki.net](mailto:kboinfo@namiki.net)

Specifications subject to change without notice